

POLYSTRETCH P8 CS MATT

TECHNICAL DATA SHEET

November 2023

Create the most spectacular shapes with PolyStretch, an ideal solution for modular, light-weight, scenic elements, display, architectural pieces and for use as a projection surface. Even with decorative holes in it, this stretch fabric keeps its shape without tearing or fraying!

» ARTICLE CODE 2979 0300 #	» WIDTH 300 cm	» LENGTH ± 60 m	» WEIGHT 210 g/m ²
--------------------------------------	--------------------------	---------------------------	---

» COMPOSITION 75% PES TCS 25% EA FR	» CARE INSTRUCTIONS PolyStretch P8 CS Matt can endure a maximum of 5 washing cycles at 60° Celsius.
--	---



» FLAME RESISTANCE AS 1530.2 AS 1530.3 DIN 4102 / B1	BS 5867 PART 2B / pass NFPA 701 / pass NF P 92-507 / M1
--	---

» TEAR STRENGTH ISO 13937-3: 2000 Warp: 26 N - Weft: 28 N	» TENSILE STRENGTH ISO 13934-1: 1999 Warp: 390 N - Weft: 330 N	» COLOUR FASTNESS TO LIGHT ISO 105-B02-1999+Am 2002 0003 (white): note 2-3 0025 (grey): note 4 0007 (black): note 5	» COLOUR FASTNESS TO CHLORINATED WATER EN ISO 105 - E03:2010 0007 (black): note 4-5
--	---	--	--

» AVAILABLE COLOURS



*COLOUR RED (0200) IS ALSO AVAILABLE IN 240 CM WIDE.