

## STRETCHTULLE

### TECHNICAL DATA SHEET

January 2024

A highly elastic mesh that stretches seamlessly up to 7.5 or even 12 metres wide. The open-weave material offers ultimate flexibility and lets you create the most amazing special effects. Mesh size: H 2 mm x W 4 mm.

» <b>ARTICLE CODE</b>	» <b>WIDTH</b>	» <b>STRETCHED WIDTH</b>	» <b>WEIGHT</b>
3521 0500 #	500 cm	± 750 cm	200 g/m <sup>2</sup>
3521 0700 #	700 cm	± 1200 cm	300 g/m <sup>2</sup>
» <b>LENGTH</b>	» <b>COMPOSITION</b>		
± 45 m	98% PES + 2% EA		

#### » FLAME RESISTANCE

StretchTulle - 3521 0500 #	StretchTulle - 3521 0700 #
NF P 92-507 / M1	NF P 92-507 / M1
EN 13773 / class 1	EN 13773 / class 1
NFPA 701 / pass	NFPA 701 / pass
GB 8624 / B2	GB 8624 / B1
AS 1530.2	
AS 1530.3	
BS 5867 PART 2B / pass	

» <b>TEAR STRENGTH</b>	» <b>TENSILE STRENGTH</b>	» <b>COLOUR FASTNESS TO LIGHT</b>	» <b>AIR PERMEABILITY</b>
ISO 13937-3: 2000 Warp: 22N - Weft: 15N	ISO 13934-1: 1999 Warp: 590N - Weft: 110N	ISO 105-B02-1999+Am 2002 note 6	EN ISO 9237 (1995) Average: 3980 l/(m <sup>2</sup> .s)

#### » AVAILABLE COLOURS

